



MULTI-FREQUENCY, MULTI-GNSS RTK & ATLAS®



Key Features

- Multi-Frequency GPS, GLONASS, BeiDou, Galileo, and QZSS
- Long-range RTK baselines up to 50 km with fast acquisition times
- Compatible with many RTK sources including Hemisphere GNSS' ROX format, RTCM, CMR, CMR+
- Mechanically and electrically (pin-for-pin) compatible with many other manufacturers' modules
- Atlas® L-band capable to 4 cm RMS
- Athena™ GNSS engine providing best-in-class RTK performance
- Serial, USB, Ethernet and CAN connectivity for ease of use and integration

Track More Signals for the Most Robust Low-Power Multi-Frequency, Multi-GNSS Solution

Track more signals for unparalleled positioning performance with Hemisphere GNSS' new Eclipse P328 OEM board. The latest technology platform enables simultaneous tracking of all satellite signals including GPS, GLONASS, BeiDou, Galileo, QZSS, and L-band making it the most robust and reliable solution for machine control. The power management system efficiently governs the processor, memory, and ASIC making it ideal for multiple integration applications.

Experience Unparalleled Accuracy and Reliability with Advanced Technology Features

The P328 is the most accurate and reliable OEM module with two new advanced technology features; aRTK™ and Tracer™. Hemisphere's all-new aRTK technology, powered by Atlas, allows the P328 to operate with RTK accuracies when RTK corrections fail. Tracer utilizes specialized algorithms to sustain positioning in the absence of correction data.

Scalable Solutions

With the Eclipse P328, positioning is scalable and field upgradeable with all Hemisphere software and service options. Utilize the same centimeter-level accuracy in either single frequency mode, or employ the full performance and fast RTK initialization times over long distances with multi-frequency, multi-constellation GNSS signals. High-accuracy L-band positioning from meter to sub-decimeter levels available via Atlas GNSS correction service.

Ease of Migration

Leverage the industry standard form factor for easy upgradeability from other manufacturers' modules.

GNSS Receiver Specifications

| | |
|---------------------------------|---|
| Receiver Type: | Multi-Frequency GPS, GLONASS, BeiDou, Galileo, QZSS, and Atlas |
| Signals Received: | GPS L1CA/L1P/L1C/L2P/L2C/L5 GLONASS G1/G2, P1/P2 BeiDou B1/B2/B3 GALILEO E1BC/E5a/E5b QZSS L1CA/L2C/L5/L1C Atlas |
| Channels: | 600 |
| GPS Sensitivity: | -142 dBm |
| SBAS Tracking: | 3-channel, parallel tracking |
| Update Rate: | 1 Hz standard, 10 Hz, 20 Hz or 50Hz optional (with activation) |
| Timing (1 PPS) | |
| Accuracy: | 20 ns |
| Cold Start: | 60 s typical (no almanac or RTC) |
| Warm Start: | 30 s typical (almanac and RTC) |
| Hot Start: | 10 s typical (almanac, RTC and position) |
| Antenna Input Impedance: | 50 Ω |
| Maximum Speed: | 1,850 mph (999 kts) |
| Maximum Altitude: | 18,288 m (60,000 ft) |

Accuracy

| Positioning: | RMS (67%) | 2DRMS (95%) |
|--|------------------|--------------------|
| Autonomous, no SA: ¹ | 1.2 m | 2.5 m |
| SBAS: ¹ | 0.3 m | 0.6 m |
| Atlas H10: ^{1,3} | 0.04 m | 0.08 m |
| Atlas H30: ^{1,3} | 0.15 m | 0.3 m |
| Atlas Basic: ^{1,3} | 0.50 m | 1.0 m |
| RTK: ¹ | 8 mm + 1 ppm | 15 mm + 2 ppm |

L-Band Receiver Specifications

| | |
|-----------------------------|----------------------|
| Receiver Type: | Single Channel |
| Channels: | 1525 to 1560 MHz |
| Sensitivity: | -130 dBm |
| Channel Spacing: | 5.0 kHz |
| Satellite Selection: | Manual and Automatic |
| Reacquisition Time: | 15 seconds (typical) |

1. Depends on multipath environment, number of satellites in view, satellite geometry, and ionospheric activity
2. Based on a 40 second time constant
3. Hemisphere GNSS proprietary
4. With future firmware upgrade and activation
5. CMR and CMR+ do not cover proprietary messages outside of the typical standard



Hemisphere GNSS
8515 E. Anderson Drive
Scottsdale, AZ 85255, USA

Phone: +1 (480) 348-6380
Toll-Free: +1 (855) 203-1770
Fax: +1 (480) 270-5070

precision@hgns.com
www.hgns.com

Communications

| | |
|---------------------------------|---|
| Ports: | 3 x full-duplex (1 x 3.3V CMOS, 1 x 3.3V CMOS with flow control, 1 x RS-232 with flow control) 1 x USB Device 1 x Ethernet 10/100Mbps 2 x CAN (NMEA2000, ISO 11783) |
| Interface Level: | 3.3V CMOS |
| Baud Rates: | 4800 - 115200 |
| Correction I/O Protocol: | Hemisphere GNSS proprietary ROX format, RTCM v2.3, RTCM v3.2, CMR ⁵ , CMR+ ⁵ |
| Data I/O Protocol: | NMEA 0183, Crescent binary ³ |
| Timing Output: | 1 PPS, CMOS, active high, rising edge sync, 10 kΩ, 10 pF load |
| Event Marker Input: | CMOS, active low, falling edge sync, 10 kΩ, 10 pF load |

Power

| | |
|---------------------------|---|
| Input Voltage: | 3.3 VDC +/- 5% |
| Power Consumption: | 1.1 W GPS (L1) 1.8 W GPS (L1/L2) and GLONASS (G1/G2) 2.9 W All Signals + L-band |

| | |
|-----------------------------|---|
| Current Consumption: | 0.33 A nominal GPS (L1) 0.55 A nominal GPS (L1/L2) and GLONASS (G1/G2) 0.88 A nominal All Signals + L-band 5 VDC maximum |
|-----------------------------|---|

| | |
|--|-------------|
| Antenna Voltage: | |
| Antenna Short Circuit Protection: | Yes |
| Antenna Gain Input Range: | 10 to 40 dB |

Environmental

| | |
|-------------------------------|---|
| Operating Temperature: | -40°C to +85°C (-40°F to +185°F) |
| Storage Temperature: | -40°C to +85°C (-40°F to +185°F) |
| Humidity: | 95% non-condensing (when in an enclosure) |

| | |
|--------------------------|---|
| Mechanical Shock: | EP455 Section 5.14.1 Operational (when mounted in an enclosure with screw mounting holes utilized) |
| Vibration: | EP455 Section 5.15.1 Random |
| EMC: | CE (IEC 60945 Emissions and Immunity) FCC Part 15, Subpart B CISPR 22 |

Mechanical

| | |
|----------------------------------|--|
| Dimensions: | 100 L x 60 W x 10 H (mm) 3.9 L x 2.4 W x 0.4 (in) |
| Weight: | 44 g (1.56 oz) |
| Status Indications (LED): | Power, GNSS lock, Differential lock, DGNSS position |
| Power/Data Connector: | 24 pin male header 2 mm pitch 16 pin male header 2 mm pitch |
| Antenna Connectors: | MMCX, female, straight |