




# MULTI-FREQUENCY, MULTI-GNSS RTK & ATLAS®



## Key Features

- Multi-Frequency GPS, GLONASS, BeiDou, Galileo, and QZSS
- Long-range RTK baselines up to 50 km with fast acquisition times
- Compatible with many RTK sources including Hemisphere GNSS' ROX format, RTCM, CMR, CMR+
- Mechanically and electrically (pin-for-pin) compatible with many other manufacturers' modules
- Atlas® L-band capable to 4 cm RMS
- Athena™ GNSS engine providing best-in-class RTK performance
- Serial, USB host (Phantom 34 only), USB device, and CAN connectivity for ease of use and integration

## Track More Signals for the Most Robust Low-Power Multi-Frequency, Multi-GNSS Solution

Track more signals for unparalleled positioning performance with Hemisphere GNSS' new Phantom 20 and 34 OEM boards. The latest technology platform enables simultaneous tracking of all satellite signals including GPS, GLONASS, BeiDou, Galileo, QZSS, IRNSS and L-band making it the most robust and reliable solution for GIS, agriculture, and machine control. The power management system efficiently governs the processor, memory, and ASIC making it ideal for multiple integration applications.

## Experience Unparalleled Accuracy and Reliability with Advanced Technology Features

The Phantom 20 and 34 are the most accurate and reliable OEM modules with two advanced technology features; aRTK™ and Tracer™. Hemisphere's aRTK technology, powered by Atlas, allows the Phantom 20 and 34 to operate with RTK accuracies when RTK corrections fail. Tracer uses specialized algorithms to sustain positioning in the absence of correction data.

## Scalable Solutions

With the Phantom 20 and 34, positioning is scalable and field upgradeable with all Hemisphere software and service options. Use the same centimeter-level accuracy in either single frequency mode, or employ the full performance and fast RTK initialization times over long distances with multi-frequency, multi-constellation GNSS signals. High- accuracy L-band positioning from meter to sub-decimeter levels available via Atlas GNSS correction service.

## Ease of Migration

Leverage the industry standard form factor for easy upgradeability from other manufacturers' modules.

## GNSS Receiver Specifications

<b>Receiver Type:</b>	Multi-Frequency GPS, GLONASS, BeiDou, Galileo, QZSS, and Atlas
<b>Signals Received:</b>	GPS L1CA/L1P/L1C/L2P/L2C/L5 GLONASS G1/G2/G3, P1/P2 BeiDou B1i/B2i/B3i/B10C/B2A/B2B/ ACEBOC GALILEO E1BC/E5a/E5b/E6BC/ ALTBOC QZSS L1CA/L2C/L5/L1C/LEX IRNSS L5 Atlas
<b>Channels:</b>	800+
<b>GPS Sensitivity:</b>	-142 dBm
<b>SBAS Tracking:</b>	3-channel, parallel tracking
<b>Update Rate:</b>	1 Hz standard, 10 Hz, 20 Hz or 50Hz optional (with activation)

### Timing (1 PPS)

<b>Accuracy:</b>	20 ns
<b>Cold Start:</b>	60 s typical (no almanac or RTC)
<b>Warm Start:</b>	30 s typical (almanac and RTC)
<b>Hot Start:</b>	10 s typical (almanac, RTC and position)

### Antenna Input

<b>Impedance:</b>	50 $\Omega$
<b>Maximum Speed:</b>	1,850 kph (999 kts)
<b>Maximum Altitude:</b>	18,288 m (60,000 ft)

### Accuracy

<b>Positioning:</b>	<b>RMS (67%)</b>	<b>2DRMS (95%)</b>
<b>Autonomous, no SA:</b> <sup>1</sup>	1.2 m	2.5 m
<b>SBAS:</b> <sup>1</sup>	0.3 m	0.6 m
<b>Atlas H10:</b> <sup>1,3</sup>	0.04 m	0.08 m
<b>Atlas H30:</b> <sup>1,3</sup>	0.15 m	0.3 m
<b>Atlas Basic:</b> <sup>1,3</sup>	0.50 m	1.0 m
<b>RTK:</b> <sup>1</sup>	8 mm + 1 ppm	15 mm + 2 ppm

## L-Band Receiver Specifications

<b>Receiver Type:</b>	Single Channel
<b>Channels:</b>	1525 to 1560 MHz
<b>Sensitivity:</b>	-130 dBm
<b>Channel Spacing:</b>	5.0 kHz
<b>Satellite Selection:</b>	Manual and Automatic
<b>Reacquisition Time:</b>	15 seconds (typical)

1. Depends on multipath environment, number of satellites in view, satellite geometry, and ionospheric activity
2. Depends on multipath environment, number of satellites in view, SBAS coverage, satellite geometry, and ionospheric activity
3. Hemisphere GNSS proprietary
4. With future firmware upgrade and activation
5. CMR and CMR+ do not cover proprietary messages outside of the typical standard



## Communications

<b>Ports:</b>	4 x full-duplex 3.3V CMOS (3 x main Serial ports, 1x differential port) 1 x USB Host (Phantom 34 only) 1 x USB Device 2 x CAN (NMEA2000, ISO 11783)
<b>Interface Level:</b>	3.3V CMOS
<b>Baud Rates:</b>	4800 - 115200
<b>Correction I/O Protocol:</b>	Hemisphere GNSS proprietary ROX format, RTCM v2.3, RTCM v3.2, CMR <sup>5</sup> , CMR+ <sup>5</sup>
<b>Data I/O Protocol:</b>	NMEA 0183, Crescent binary <sup>3</sup>
<b>Timing Output:</b>	1 PPS, CMOS, active high, rising edge sync, 10 k $\Omega$ , 10 pF load
<b>Event Marker Input:</b>	CMOS, active low, falling edge sync, 10 k $\Omega$ , 10 pF load

### Power

<b>Input Voltage:</b>	3.3 VDC +/- 5%
<b>Power Consumption:</b>	< 1.8 W all signals + L-Band
<b>Current Consumption:</b>	545 mA
<b>Antenna Voltage:</b>	5 VDC maximum
<b>Antenna Short Circuit Protection:</b>	Yes
<b>Antenna Gain Input Range:</b>	10 to 40 dB

### Environmental

<b>Operating Temperature:</b>	-40°C to +85°C (-40°F to +185°F)
<b>Storage Temperature:</b>	-40°C to +85°C (-40°F to +185°F)
<b>Humidity:</b>	95% non-condensing (when in an enclosure)
<b>Mechanical Shock:</b>	EP455 Section 5.14.1 Operational (when mounted in an enclosure with screw mounting holes utilized)
<b>Vibration:</b>	EP455 Section 5.15.1 Random
<b>EMC:</b>	CE (IEC 60945 Emissions and Immunity) FCC Part 15, Subpart B CISPR 22

### Mechanical

<b>Dimensions:</b>	
<b>Phantom 20:</b>	72 L x 41 W x 10 H (mm) 2.8 L x 1.6 W x 0.4 H (in)
<b>Phantom 34:</b>	71 L x 41 W x 10 H (mm) 2.8 L x 1.6 W x 0.4 H (in) 22 g (0.79 oz)
<b>Weight:</b>	
<b>Status Indications (LED):</b>	Power, GNSS lock, Differential lock, DGNSS position
<b>Power/Data Connector:</b>	
<b>Phantom 20:</b>	20-pin male header, 0.08" (2 mm) pitch
<b>Phantom 34:</b>	34-pin male header, 0.05" (1.27 mm) pitch
<b>Antenna Connectors:</b>	MCX, female, straight

## Hemisphere GNSS

8515 E. Anderson Drive  
Scottsdale, AZ 85255, USA

Phone: +1 (480) 348-6380  
Toll-Free: +1 (855) 203-1770  
Fax: +1 (480) 270-5070

precision@hgns.com  
www.hgns.com