

G3ANT-4XXX ANTENNA FAMILY

Mini ARINC GNSS Antenna

The G3Ant-4XXX product family provides assured Global Navigation Satellite System (GNSS) signal reception through multi-constellation reception. This G3 antenna includes coverage across three frequency bands: GLONASS L1, GPS L1 plus Galileo E1, and L-Band with B1 BeiDou. This product family is designed to a Mini ARINC mounting footprint for easy integration onto new and existing platforms. The rugged enclosure can withstand the harsh environmental conditions seen in military, aerospace and other applications.

Antcom can customize this product family to meet your specific requirements. Please contact us for more information about customization options.



- Rugged GNSS antenna
- Mini ARINC form factor is small and lightweight
- Many standard options available and customizable if required

FEATURES

- GPS L1, Galileo E1, GLONASS L1 and L-Band
- Mini ARINC product footprint
- Passive or active (amplified) configurations available
- Active configurations offer 2-stage integrated bandpass filtering with diode limiters
- Connector options available
- Paint color options available



OPTIONS

COLOR

- Gloss White
- Lusterless Gray
- Camo Green
- Lusterless Black
- Tan

CONNECTOR

- S: SMA
- T: TNC
- TB: TNC-Bulkhead
- N: Type-N

LNA GAIN

- With 33 dB LNA
- Without LNA

"These items are controlled by the U.S. Government and authorized for export only to the country of ultimate destination for use by the ultimate consignee or end-user(s) herein identified. They may not be resold, transferred or otherwise disposed of to any other country or to any person other than the authorized ultimate consignee or end-user(s), either in their original form or after being incorporated into other items, without first obtaining approval from the U.S. Government or as otherwise authorized by U.S. law and regulations."

ELECTRICAL

Frequency Range:	
L-Band	1545 - 1610 MHz
B1 BeiDou	1561.098 ± 10 MHz
L1 GPS	1575.42 ± 12 MHz
E1 Galileo	1575.42 ± 17 MHz
L1 GLONASS	1609 ± 7.0 MHz
VSWR	<2.0:1
Impedance	50 ohms
Polarization	RHCP

MECHANICAL & ENVIRONMENTAL

Designed to:

Weight	6.53 oz
Temperature	-55°C TO +85°C
Altitude	70,000 ft
Vibration	>30 Grms

TYPICAL LNA PERFORMANCE

LNA Gain	See Options Table
LNA Noise Figure	3.5 dB
LNA P1dB Out	+13 dBm
LNA DC Power	(3.8 - 15) V
	<70 mA

LIMITING & FILTERING

Power Handling	1 Watt CW
----------------	-----------





Phone: +1-310-782-1076 Fax: +1-310-782-1086 Email: sales.pi.antcom@antcom.com Web: antcom.com

©2020 ANTCOM CORP. ALL RIGHTS RESERVED. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

REVISION B JANUARY 2021

