

FOGPSAL

Fiber Optic GPS Antenna Link Technical Product Data



Description

The Fiber Optic GPS Antenna Link is a complete system that allows you to convert the GPS Carrier from RF to Light, transmit it up to 10 Kilometers if need be then reconvert it back to RF to be received by the GPS receiver.

Components

- Roof Antenna
- Transmitter Power Supply
- Transmitter Preamp
- Fiber Optic Transmitter
- Fiber Optic Receiver
- Receiver Power Supply

Fiber Optic Transmitter

| Electro Optic Characteristics | |
|--|----------------------|
| Optical Pout | 1mW min. |
| Wavelength | 1310+/-30 |
| RF Characteristics | |
| Modulation Bandwidth | 1000-1700 MHz |
| Amplitude Flatness | 1.5dB typical |
| Input VSWR (50 Ohms) | 2.0:1 max |
| MW/ma@1200Mhz | 0.1mW/ma min |
| 1dB Compression | -25 dBm |
| Power | 110/220 or 28-36 VDC |
| Physical Characteristics | |
| Dimensions-Indoor Rack Mount | Height 1.75" |
| | Width 8.0" |
| | Length 17.0" |
| Dimensions-Sealed Outdoor Waterproof Box | Height 4.17" |
| | Width 7.72" |
| | Depth 12.0" |

Fiber Optic Receiver

| Electro Optic Characteristics | | | | | | |
|---|----------------------|----------------------------|-----|------|--|--|
| | Min | Тур | Max | Unit | | |
| Gain | 20 | 25 | 30 | dB | | |
| Optical Pout | 1mW min. | | | | | |
| Wavelength | 1310+/-30 | | | | | |
| Responsiveness | | 0.85 @ 1300 typical | | | | |
| RF Characteristics | | | | | | |
| Available Bandwidth | | 1000-1700 MHz | | | | |
| Amplitude Flatness | | 1.5dB typical | | | | |
| Output VSWR (50 Ohms) | | 2.0:1 max | | | | |
| Power | 110/220 or 28-36 VDC | | | | | |
| Physical Characteristics | | | | | | |
| Dimensions-Indoor Rack Mount Fiber Optic Receiver | | Height 1.75' Width 8.0' | | | | |
| | | Length 17.0 | | | | |

| Link Characteristics | | |
|---------------------------------|----------------------------|--|
| Available Bandwidth | 1000-1700 MHz | |
| Link Loss | 15 dB typical | |
| Carrier/Noise (30khz BW) | 15 dB min with input drive | |
| | level at 70 dBm | |
| 3 rd Order Intercept | 22dBm | |
| Environmental Conditions | | |
| Operating Temperature | -25 to +70 (deg C) | |
| Storage Temperature | -30 to +75 (deg C) | |
| Mechanical | | |
| Optical Connectors | FC/APC Fiber S/M 9/125 | |
| RF Connectors | N-Type | |

Applications

- GPS base stations with long antenna cable runs
- Run the GPS carrier to multiple GPS timing boards throughout a company
- Run GPS throughout an aircraft
- Satisfies the requirement of supplying multiple GPS receivers with a carrier, spread over a great distance
- For R&D facilities, supplies a GPS carrier to a multitude of engineers and technicians with only one antenna on the roof.